

RE		7		C		-L	
		< Heat Rating >					
RE	Plug for rotary engines	5	Hot type ↑ ↓ Cold type	A,B,C...Suffix code		-L	L-side
SD	Plug for rotary engines (Semi-surface discharge gap)	6				-T	T-side
		7					
		8					
		9					
		10					
		11					

HB		6		A				IX		-11		P	
		< Heat Rating >		Thread dimensions / Hex. size						< Spark gap >			
HB	HYBD ^R (3-ground-electrode hybrid type)	4	Hot type ↑ ↓ Cold type	A	14.0	20.5mm	Gasket	16.0	IX		-8	0.8mm	
		5		B	14.0	19.0mm	Gasket	16.0			-9	0.9mm	
		6								-10	1.0mm		
		7								-11	1.1mm		
		8								-13	1.3mm		
		9								-14	1.4mm		
		10								-15	1.5mm		

DF		6		H				-11		A	
		< Heat Rating >		Thread dimensions / Hex. size				< Spark gap >			
DF	High ignitability plug :Double fine electrodes	4	Hot type ↑ ↓ Cold type	H	12.0	26.5mm	Gasket	14.0	-8	0.8mm	A,B,C...Suffix code
		5							-9	0.9mm	DF6H-11A;reach 28.0mm
		6							-10	1.0mm	DF6H-11B;reach 26.5mm
		7							-11	1.1mm	
		8							-13	1.3mm	
		9							-14	1.4mm	
		10							-15	1.5mm	